

## Switches for the future photovoltaic market

The relevance of renewable energy for the world gains in importance each day – photovoltaic plays a prominent leading part in this process. To further the development of this market and to guarantee a safe handling of photovoltaic systems, Sälzer has advanced its DC rated disconnect switches. These are audited according to IEC 60947-3 and therefore applicable for every photovoltaic system conforming to IEC 60364-7-712:2002.

Sälzer Electric GmbH  
Matthiasstraße 16  
D-57482 Wenden (Germany)

Phone +49 (0) 2762 614-110  
Fax +49 (0) 2762 614-100  
[info@saelzer.de](mailto:info@saelzer.de)  
[www.saelzer.com](http://www.saelzer.com)

## Maximum protection for photovoltaic systems

Semiconductor cells are the core component of a photovoltaic panel. Several panels combined make a PV string or solar module. Photons emitted by the sun generate direct current in the PV panels, which can be measured all the way down to the inverter box. For maintenance purposes or in case of emergencies, it is therefore necessary to disconnect the DC load (according to IEC 60364-7). This termination can either be achieved by using connectors or preferably DC rated disconnect switches. With their safe switching technology Sälzer DC disconnect switches ensure maximum protection in photovoltaic systems.

We are constantly aiming to expand our range on DC rated switches through new developments.

Info

**For detailed information please contact our distribution centre.**



## Switch on the sun!

Sälzer load breaking switches for your photovoltaic system

# Load breaking switches for photovoltaic

## Polycarbonate Enclosures

- IP66 insulated enclosure (polycarbonate)
- With N-padlock device
- Main/Emergency-Off Switch (yellow/red) or Main Switch (black)



## Base Mounting Switches

- For panel applications and distribution boards
- With M-handle or padlockable with V-handle
- Main Switch (black)



250 V DC	450 V DC	500 V DC	650 V DC	800 V DC	Enclosure size	Main/Emergency-Off Switch (N-padlock device yellow/ red)	Main Switch (N-padlock device black)
32 A	20 A	16 A			175 x 115 x 100 mm	H226-81400-710N4	H226-81400-710N1
		20 A			175 x 115 x 100 mm	H233-81400-710N4	H233-81400-710N1
	25 A				175 x 115 x 100 mm	H233-81500-710N4	H233-81500-710N1
		25 A			175 x 115 x 100 mm	B250-81500-710N4	B250-81500-710N1
	32 A				175 x 115 x 100 mm	B250-81400-710N4	B250-81400-710N1
			20 A		175 x 115 x 100 mm	H226-81600-720N4	H226-81600-720N1
		32 A	25 A		250 x 160 x 120 mm	B240-81600-761N4	B240-81600-761N1
			32 A		250 x 160 x 120 mm	B250-81600-761N4	B250-81600-761N1
			63 A		320 x 220 x 180 mm	H408-81700-977N4	H408-81700-977N1
				20 A	250 x 160 x 120 mm	H226-81800-761N4	H226-81800-761N1
				25 A	280 x 190 x 130 mm	B240-81800-740N4	B240-81800-740N1
				32 A	280 x 190 x 130 mm	B250-81800-740N4	B250-81800-740N1
				50 A	320 x 220 x 180 mm	H408-81800-977N4	H408-81800-977N1

250 V DC	450 V DC	500 V DC	650 V DC	800 V DC	Main Switch (M-handle black)	Main Switch with padlockable handle (V-handle black)
32 A	20 A	16 A			H226-81400-026M1	H226-81400-026V1
		20 A			H233-81400-026M1	H233-81400-026V1
	25 A				H233-81500-026M1	H233-81500-026V1
		25 A			B250-81500-026M1	B250-81500-026V1
	32 A				B250-81400-026M1	B250-81400-026V1
			20 A		H226-81600-026M1	H226-81600-026V1
		32 A	25 A		B240-81600-026M1	B240-81600-026V1
			32 A		B250-81600-026M1	B250-81600-026V1
			63 A		H408-81700-126M1	H408-81700-126V1
				20 A	H226-81800-026M1	H226-81800-026V1
				25 A	B240-81800-026M1	B240-81800-026V1
				32 A	B250-81800-026M1	B250-81800-026V1
				50 A	H408-81800-126M1	H408-81800-126V1

All load breaking switches from Sälzer switch the plus(+) and minus(-) pole simultaneously.